| Section 6.4.78   |         | (580.01) |
|--|---------|----------|
| RESIDENTIAL 8  |         | R8       |
| Maximum Size of Buildings and Structures                     |         |          |
| Accessory buildings - combined floor area                    | 75 m²   |          |
| Height -Principal building                                   |         |          |
| - Interior heated space                                      | 7.3 m   |          |
| ·  | 9.0 m   |          |
| - Ridge of gable, hip or gambrel sloped roof                 | 9.0 111 |          |
| - Mansard roof   | 2.2     |          |
| - deck line  | 8.0 m   |          |
| - top of roof  | 9.0 m   |          |
| - Flat roof  | 8.0 m   |          |
| -Accessory Building  | 4.5 m   |          |
| Parcel Coverage  | 35%     |          |
| Minimum Setback Requirements                                 |         |          |
| Front lot line Rear lot line                                 | 8.0 m   |          |
| - Principal building   | 3.0 m   |          |
| - Accessory building   |         |          |
| -floor area more than 10m <sup>2</sup> or over 3 m in height | 1.5 m   |          |
| -floor area no more than 10m <sup>2</sup> and no more than   | _       |          |

- Principal building - Accessory building

Exterior side lot line

Interior side lot line

3 m in height

-floor area more than 10m<sup>2</sup> or over 3 m in height -floor area more than 10m<sup>2</sup> and no more than 1.5 m

0 m

4.5 m

3 m in height 0 m

Provided that the aggregate total of the minimum distances from each interior side lot line to the principal building shall not be less than 4.5 meters.

## Note:

For information regarding permitted uses, refer to "Land Use Contract Authorization Bylaw No. 157, 1974" and amendments thereto.